

A PavementGroup Brand

STRATOS CAPACITIES 400, 600, 1000, 1500, 2000 gal.

STANDARD FEATURES INCLUDED:

- CHOOSE TRAILER MOUNTED 400, 600, 1000 gals.
- CHOOSE TRUCK Mountable 400, 600, 1000, 1500, 2000 gals.
 - CHOOSE Truck mount, Skid mount, Hook style
 - NEW!! NO CDL Required 1500-gallon truck mount
- Low Profile elliptical, baffled, expansion overflow tube
- Diesel Heated Beckett 350,000 BTU diesel burner(s)
- Thermostatic material temperature controls, digital display
- Temperature gauge, analog
- Gas engine, electric start+ pull start, approx. 14HP, engine type based on availability (Briggs Vanguard, else Kohler, or Honda)
- Alternator charging circuit
- Deep cell battery, battery case, & voltmeter
- 60GPM Viking Pump
- Hand applicator wand with on/off valve, foot valve, swivel
- 50' Hose reel, 34", Hannay high-end Industrial spring rewind reel
- Material level gauge, with mechanical indicator
- Flush system with 10 Gallon tank
- Insulation 2" mineral wool, aluminum outer shell
- Ladder, double locking 20" manway, strainer basket
- Bottom 2" cleanout, drain valve
- Electric brakes on all axles, electric break-away kit
- Electrical IP64 rated NEMA waterproof enclosures & connectors
- DOT compliant LED lights (brake, turn, marker, running)
- Heavy duty, adjustable tongue jack
- 5-position, 12" (30cm) adjustable hitch, up to 29" tow height
- Pintle ring, Black frame & fenders, safety yellow tank
- Trailer; Single-axle (400 gal), double-axle (600 gal +)
- Axles each at 7,000 lbs (3,175kg)
- 600gal GVWR=8,907 LBS, 1000gal GVWR=13,216LBS
- Trailer is DOT & NATM compliant
- Wheels 16", 1.5cm, 8 lug, chains, tires ST235/80R16-E, 10-ply Components, brands, design are subject to change without notice



1525 Western Ave., Albany, NY 12203 518 218-7676

Industry Leading 18-Month Warranty!

OPTIONS

- Spray-bar: 8',12', 14', 16' manual on/off with rear operator's platform, railing and safety chain.
- Computer Monitor: spray on-off, gal/min, speed, gal applied, target-speed; for when precise application rate is a must.
- Remote spray-bar on-off: electric over pneumatic valve with air compressor and deep-cell battery package
- Dual Flow, Full-Circulation pneumatic spray-bar
- Strobe Light, LED, amber, mounted
- Spare tire, mounted
- Hydraulic brakes
- Hitch Extension 24"
- Overnight electric heat maintainer: 220V, 3-phase, 6,000 W

Dimensions:

DMT-1000 Gallon: L17' x W 7' x H 7.25', at 4872 lbs.

L 518 cm x W 213 cm x 222 cm, at 2210 kg

DMT-600 Gallon: L 16' x W 7' x H 6.5', at 3470 lbs.

L 488 cm x W 213 cm x 198 cm, at 1574 kg

DMT-400 Gallon: L 14' x W 7' x H 6.5', at 2665 lbs.

L 427 cm x W 213 cm x 198 cm, at 1209 kg











Truck & Trailer - computer monitor, remote on/off, radar guided application rate





1525 Western Ave., Albany, NY 12203 518 218-7676

You Asked...We Listened!

MORE Mounting Options: Truck, skid, hook MORE Capacities: 400, 600, 1000, 1500, 2000

GFT IT NOW! DMS-1500 gal No CDL required!

Our alternator driven deep cell charging circuit eliminates the need for auxiliary truck power!





Computer Monitor

Gals/Min, Applied, Speed, Real-time & historical data

Full Circulation. Dual Flow Spray bar. Remote

Satisfied CUSTOMERS

Over 400 and counting... Join the STRATOS team!

We ship Internationally



"Machine is great!"

Derrick Buescher, Brookfield Township MO

"Works really well ... saved us 30-40k over 2 years" Keith Hutson, Beardstown, IL

"A well-built machine ... great follow up support" Paul Howland, OR DOT

"The Stratos DMT-1000 is the single best investment I have ever made for my business"

Allen Buchanan, North TX Paving

"You gave excellent service and response"

Nicoll Bros, E Sussex England UK

"We love the machine"

Don Allen, City of Atoka OK

"Machine is great ... we use it a lot ... sprayed about 20k gals this past year ... like it very much"

Tim Boots, Perry Township, PA

"Best price I found, less than 2 wks to get it"

Billy Snell, Billy's Asphalt Paving, TX

"Very reliable, you can heat it up going down the road,

I love it" Mike Greenough, Greenough Paving, NY

