

1525 Western Ave., Albany, NY 12203 518 218-7676



A PavementGroup Brand

# 400, 600, 1000, 2000 Gallon STRATOS Asphalt Distributors

#### **STANDARD FEATURES:**

- Trailer mounted capacities: 400, 600, 1000 gallon
- Skid mounted capacities: 400, 600, 1000, 2000 gallon
- Baffled tank, low profile, elliptical, expansion overflow tube
- Beckett 350,000 BTU diesel burner, thermostatic controls
- Honda GX270 8.3HP gasoline engine (optional GX390 11.5)
- Viking 32gpm pump (optional 60gpm)
- Hannay Industrial spring rewind hose reel, 50', ½" hose
- Hand applicator wand with on/off valve and foot valve
- Material level gauge, temperature gauge
- Cleanout/flush tank, 10 Gallons
- Ladder, double locking 20" manway, strainer basket
- 2" bottom cleanout drain with valve
- Trailer; Single-axle (400 gal), double-axle (600, 1000 gal)
- Axles each at 7,000 lbs (3,175kg)
- 600gal GVWR=8,907 LBS, 1000gal GVWR=13,216LBS
- Electric brakes on all axles, break-away kit
- Wheels 16", 1.5cm, 8 lug, chains, tires ST235/80R16-E, 10 ply
- DOT compliant lights (brake, turn, marker, running)
- Heavy duty, adjustable tongue jack
- 5-position, 12" (30cm) adjustable hitch, up to 29" tow height
- Pintle ring
- Black frame & fenders, safety yellow tank
- Trailer is DOT & NATM compliant
- Electrical IP64 rated NEMA waterproof enclosures & connectors
- 15 MONTH WARRANTY!

Components & design are subject to change without notice

#### **Dimensions:**

DMT-1000 Gallon: L16' x W 7' x H 7.25', at 3663 Lbs L 486 cm x W 213 cm x 222 cm, at 1648 kg DMT-600 Gallon: L 15.6' x W 7' x H 6.5', at 3370 Lbs L 406 cm x W 180 cm x 203 cm, at 1516 kg DMT-400 Gallon: L 13.4' x W 7' x H 6.6', at 2665 Lbs L 409 cm x W 213 cm x 201 cm, at 1200 kg DMS-400, 600, 1000, 2000: Call for engineering drawing









#### **OPTIONS**

- DMS Model; Skid mounted tank for truck or trailer mounting
- NEW! Computer Monitor, spray on/off, gal/min, speed, gal applied
- Spray-bar; 8', 12', 14', 16' with rear operator's platform
- Insulation; 2" mineral wool, aluminum outer shell
- Remote controlled spray-bar, electric over pneumatic valve with air compressor and battery package
- 60 GPM Pump, Honda GX390, 11.5 HP gas engine, 6" cutoffs
- Overnight electric heat maintainer: 220V, 3-phase, 6,000 W
- Electric start engine with battery and alternator
- 3/4" hose reel, 3/4" hose and applicator wand
- Strobe Light (LED, amber, mounted)
- LED lighting
- Spare tire, mounted













1525 Western Ave., Albany, NY 12203 518 218-7676



## **INTRODUCING STRATOS DMS-2000**

**NEW! Computer Monitor** 

### by PavementGroup

2000 Gallon Asphalt Distributor, Skid-Mounted, Double Burner, Insulated







**Stratos CUSTOMERS**