

SafetyFlex Replacement Electric Hoses are compatible with all models of crack filling machines and superior to all OEM hoses. Replace your Crafcro, Cimline, Seal Master, Marathon, Spaulding, Bearcat and other OEM hoses, with a superior hose at an affordable price.

Last 4 to 8 x Longer Than OEM Hoses * Lightweight

Tightest Bend Radius * No Flow Restrictions

Improved Safety * Not Hot to the Touch

Highlights

- Half The Weight Of Rubber Hoses
- Removable Hose Cover For Inspection / Replacement
- Shroud Completely Contains Material In Event Of Hose Leak Or Failure.
- Integrated Hose Swivel Reduces Weight 3 Lbs
- Reduced Operator Fatigue
- Stronger Than Rubber Hoses

Hose Specifications

- Electrically Heated Material Hose
- Hose Weight At Under 25 Lbs
- 15' (457cm) And 20' (609cm) Lengths Available
- Insulated
- Braided Hose Core
- Flexible 8" Bend Radius Empty
- Flexible 12" Bend Radius With Material Inside
- Lightweight, 15 Lbs Lighter Than Crafcro Hose
- Uses 6 Independent Heating Elements
- Heating Elements Each Independently Wired. If A Heating Element Breaks The Remaining Elements Will Continue To Function, Keeping You Operational
- Safety Shroud With Crimped Ends
- Removable Hose Shroud With Quick Connect Pin
- Continuous Service Temperature At 455 F (233c)
- Intermittent Temperature To 505 F (263c)
- Working Pressure 1050 Psi
- Test Pressure 1525 Psi
- Burst Pressure 4100 Psi
- Minimum Bend Radius 5.5 Inches (14cm)
- Integrated Male Swivels On Each End
- Quick Remove Pin Release Hose Cover

